



Oil Savers:

The Model 'V' Sand Cup is an efficient, single lip traditional cup used in high sand ratio swabbing where the number of cups can be varied to fit any application.

This cup is specifically designed to lift fluids containing a high concentration of suspended sand; however, it can also be used for lifting ordinary light loads.

Oil Savers Features:

- Black - 60 Durometer for regular use
- Blue - 40 Durometer soft for cold climate operation
- Various Wireline sizes available

Wireline Size
5/16" Blank
7/16"
9/16" (Fits 3/8" to 5/8")
Blank Rubber

Oil Savers



Model EE



Model H/HD



Quality Product | Exceptional Service

Guiberson Hydraulic Wireline Oil Savers - Specifications								
standard					metric			
Description	type and size				type and size			
	H'	HD'	HS5'	HS10'	H'	HD'	HS5'	HS10'
	20 in.	29 in.	20 in.	20 in.	508 mm	736.6 mm	508 mm	508 mm
Approximate Weight:								
saver complete	92 lb	117 lb	92 lb	96 lb	41.73 kg	53.07 kg	41.73 kg	43.54 kg
saver only	48 lb	73 lb	48 lb	52 lb	21.77 kg	33.11 kg	21.77 kg	23.59 kg
pump & hose	44 lb	44 lb	44 lb	44 lb	19.96 kg	19.96 kg	19.66 kg	19.96 kg
i.d. less rubber & bushings	1-3/16 in.	1-13/16 in.	1-13/16 in.	1-7/16 in.	46.04 mm	46.04 mm	46.04 mm	36.51 mm
fluid capacity	6 pints	6 pints	6 pints	6 pints	2.84 l	2.84 l	2.84 l	2.84 l
rubber cross-sectional area	9.35 sq. in.	9.35 sq. in.	9.35 sq. in.	2.98 sq. in.	6032.3 mm ²	6032.3 mm ²	6032.3 mm ²	1922.6 mm ²
blank - 5/16 in. line size	-	-	-	2.90 sq. in.	-	-	-	1871.0 mm ²
3/8 in. - 5/8 in. line size	9.14 sq. in.	9.14 sq. in.	9.14 sq. in.	-	5896.8 mm ²	5896.8 mm ²	5896.8 mm ²	-
3/4 in. - 1 in line size	8.63 sq. in.	8.63 sq. in.	8.63 sq. in.	-	5567.7 mm ²	5567.7 mm ²	5567.7 mm ²	-
Thread Connection:								
2-3/8 in. O.D.	8rd eue	8rd eue	8rd eue	8rd eue	-	-	-	-
2-7/8 in. O.D.	8rd eue	8 rd eue	8 rd eue	8 rd eue	-	-	-	-
3-1/2 in. O.D.	l.p. 8v	l.p. 8v	l.p. 8v	l.p. 8v	-	-	-	-
pump working pressure	1500 psi	1500 psi	1500 psi	1500 psi	10,350 kpa	10,350 kpa	10,350 kpa	10,350 kpa
hose length	50 ft	50 ft	50 ft	50 ft	15.24 m	15.24 m	15.24 m	15.24 m
Test Pressure	1500 psi	1500 psi	1500 psi	1500 psi	10,350 kpa	10,350 kpa	17,250 kpa	c



Quality Product | Exceptional Service

Guiberson Hydraulic Wireline Oil Savers - Part Numbers			
bushing with clips:			
clip only	44811	44811	44811
blank - 5/16 in.	42878	42878	42878
3/8 in. - 5/8 in.	46176	46176	39671
7/16 in.	-	-	-
3/4 in. - 1 in.	41571	41571	41571

* protect disconnected hose from dust and contamination

** Available on request

Type 'H' & 'HD' Guiberson Hydraulic Wireline Oil Savers - Part Numbers			
Description	Quantity required		
		H'	HD'
base	1	-	-
2-3/8 in. 8rd eue pin	-	40624	40624
2-7/8 in. 8rd eue pin	-	40623	40623
3" in l.p. 8v pin	-	40726	40726
body	1	39670	40274
*bushing with clips	2 sets	-	-
blank - 5/16 in.	-	42878	42878
3/8 in. - 5/8 in.	-	46176	46176
3/4 in. - 1 in.	-	41571	41571
gate	1	39672	39672
bushing spacer	1	-	40275
housing	1	40617	40617
housing bushing	1	31742	31742
housing nipple	1	59064	59064
housing nose	1	40629	40629
housing plug	1	13550	13550
housing street elbow	1	40639	40639
ram	1	40622	40622
redressing tool	1	40642	40642
**rubber	1	-	-
blank - 5/16 in.	-	42883	42883
3/8 in. - 5/8 in.	-	39675	39675
3/4 in.	-	41572	41572
spring	1	39676	39676
yoke	1	27484	27484
yoke retainer pin	1	54509	54509
hose assembly - 50 ft mea	1	40631	40631
coupler	-2	40630	40630
repair kit - mea	1	53728	53728
base o-ring	-1	16589	16589
body o-ring	-1	25790	25790
housing o-ring	-1	17468	17468